Unified constitutive model for granular-fluid mixture in quasi-static and dense flow regimes

Xiaogang Guo¹, Chong Peng², Wei Wu^{2*}, Yongqi Wang³

¹ *Institute of Geotechnical Engineering, Zhejiang University, Yuhangtang Road 866, 310058 Hangzhou, China*

² *Institute of Geotechnical Engineering, University of Natural Resources and Life Sciences, Vienna, Feistmantelstrasse 4, 1180 Vienna, Austria*

³ *Chair of Fluid Dynamics, Department of Mechanical Engineering, Technical University of Darmstadt, Otto-Berndt-Strasse 2, 64287 Darmstadt, Germany*

Abstract

Most granular materials encountered in nature and industry lie either in the quasi-static regime or the intermediate dense flow regime. Debris materials are a typical granular material with viscous interstitial fluid, and shows solid-like behaviors before failure and fluid-like behaviors after failure. Based on Bagnold's pioneering work on granular-fluid flows, we propose a framework for constitutive model development, which has an additive form. Based on this framework, a unified constitutive model for granular-fluid material in the quasi-static and dense flow regimes is developed. The main intergranular interactions and granular-fluid interactions controlling the mechanical behaviors are taken into account using the Mohr-Coulomb model and a Bagnold-type relation. Dry granular flows in three simple configurations, i.e., plain shear, vertical chute flow and flow on an inclined plane, are studied. Analytical solutions based on the presented unified model are obtained. Comparisons between results from the presented model and the $\mu(I)$ model indicate that the explicit partition of frictional and collisional stress components provides insights in dense granular flows. In addition, the new model is used to predict the stress-strain relations in two annular shear tests. The applicability and advantages of the unified model are discussed.

Keywords: constitutive model, granular-fluid flows, solid volume fraction, dynamic viscosity, dense flow regimes

*Corresponding author. E-mail: wei.wu@boku.ac.at

13 1. Introduction

14 Granular flows are widely presented in industry and nature, e.g., raw material pro-
15 cessing and geophysical flows. With different material properties, external loads and
16 boundary conditions, granular materials can behave like solid, fluid or gas. Debris flows
17 are typical granular flows with viscous interstitial fluid which show solid-like behaviors
18 before failure and fluid-like behaviors after failure. They are normally treated as a fluid
19 continuum with microstructural effect in constitutive modeling for the fluid-like behav-
20 iors [1, 2]. However, a constitutive model that can describe both the solid-like and fluid-
21 like behaviors is required for a complete simulation of the process from quasi-static state
22 to the fast flowing state. In the quasi-static regime, the solid-like granular materials can
23 be sufficiently described using plasticity theories in soil mechanics, whereas constitutive
24 equations based on kinetic theory have been proposed for the gas regime [3]. However,
25 most granular flows lie neither in the slowly shearing quasi-static regime, nor in the fully
26 collisional gas regime. In the intermediate flow regime, the granular volume fraction is
27 close to its critical value; thus, the flows can be considered incompressible. This flow
28 regime is usually referred to as dense flow regime in literature.

29 In the dense flow regime, the granular material behaves like a liquid dominated by
30 micromechanics of the granular mass [4]. Two distinct features are observed for dense
31 granular-fluid flows. The first is that there exists a threshold yield stress below which
32 the granular media stops flowing; the second is that the granular-fluid flows are shear-
33 rate-dependent. These two features arise from three types of dominant interactions in
34 dense granular-fluid flows: frictional contacts and collisions between solid particles, and
35 viscous drag forces between solid particles and the interstitial fluid. The continuously
36 evolving network of frictional contacts result in the frictional behaviors in the dense
37 granular flows, whereas the viscous rate-dependent behavior has its source in the fluid
38 viscosity and the particle collisions. Which interaction is more dominant depends on
39 several factors, e.g., material property, external load and boundary condition.

40 In a pioneering work on a gravity-free dispersion of solid spheres sheared in Newto-
41 nian liquids, which can be considered as a simple shear test shown in Figure 1, Bagnold

Figure 1: Schematic of a simple shear test.

[5] proposed a constitutive model in which the shear stress has the relation

$$T_v = 2.25\lambda^{\frac{3}{2}}\mu \frac{dU}{dy} = k_1 \frac{dU}{dy} \quad (1)$$

in the so-called 'macro-viscous' regime and

$$T_i = 0.042\rho_s(\lambda d)^2 \left(\frac{dU}{dy}\right)^2 \sin\alpha_i = k_2 \left(\frac{dU}{dy}\right)^2 \quad (2)$$

in the 'grain-inertia' regime, respectively. In the above expressions, μ is the dynamic viscosity of the interstitial fluid; ρ_s and d are the material density and the mean diameter of the grains, respectively; dU/dy denotes the shear strain rate; the tangent of α_i corresponds to the ratio between the shear and normal stress in the grain-inertia regime; λ is the linear concentration defined by

$$\lambda = \frac{d}{s} = \left[\left(\frac{C_0}{C} \right)^{\frac{1}{3}} - 1 \right]^{-1}, \quad (3)$$

where s is the free distance between two particles, C is the mean solid volume fraction, and C_0 is the maximum possible solid volume fraction when $\lambda \rightarrow \infty$ ($s = 0$). In Bagnold's case, an analytical value for spheres, 0.74, was employed for C_0 . In general cases, the maximum measured solid volume fractions were found related to the size of the particles and the container dimensions. Usually, C_0 is replaced by the asymptotic limit of the maximum measured solid volume fraction C_∞ as the container dimensions approach infinity

55 [6].

56 A dimensionless value termed 'Bagnold number' is defined as

$$B = \frac{\lambda^{\frac{1}{2}} \rho_s d^2 (dU/dy)}{\mu} \propto \frac{T_i}{T_v} \quad (4)$$

57 to characterize the granular flow regimes as macro-viscous ($B < 40$), grain-inertia ($B >$
58 450), or a transitional state ($40 \leq B \leq 450$) between the two limits. The viscosity of
59 the interstitial fluid and the particle collisions are believed to be dominant factor in the
60 macro-viscous regime and grain-inertia regime, respectively.

61 The normal stress P is observed proportional to the shear stress T with a constant
62 ratio, 0.75, in the macro-viscous region which decreases progressively through the tran-
63 sition region, till reaches another constant value at about 0.32 in the grain-inertia region.
64 It is formulated as

$$\frac{T_v}{P_v} = \tan \alpha_v = 0.75 \quad (5)$$

65 in the macro-viscous region and

$$\frac{T_i}{P_i} = \tan \alpha_i = 0.32 \quad (6)$$

66 in the grain-inertia region, where the tangents of α_v and α_i are the stress ratios in different
67 regimes and related to the material properties. In Bagnold's experiments, the density of
68 the solid particles is equal to that of the interstitial fluids. The effect of gravity was elimi-
69 nated, and therefore no yield stress was observed in the experiment. This setup highlights
70 the effect of the fluid viscosity and the particle collisions on the flowing behaviors after
71 failure. The models developed based on the experimental observations never take yield
72 criterion into account and cannot be applied to describe the solid-like behaviors before
73 flowing. In addition, the constitutive relations of (1) and (2) are developed for both the
74 specific flow regimes. The constitutive model for the transition region is unknown, and
75 the two flow regimes are not unified in a constitutive framework. Bagnold's model cannot
76 achieve a complete description of the stress state in the process from the quasi-static state
77 to the flowing state. The transition between the two flow regimes cannot be investigated
78 consequently.

79 Another widely accepted constitutive model for dense granular flow regime is the

80 $\mu(I)$ model [7]. It employs an overall phenomenological frictional coefficient related
81 to a dimensionless 'inertial number'. Frictional contact and collision are not explicitly
82 considered in this model. Furthermore, as it is developed for dry granular flow, the drag
83 force imposed on the solid particles by the viscous interstitial fluid is not taken into
84 account. Boyer et al. [8] extended this model to general cases with viscous interstitial
85 fluids. However, the mechanical behaviors inside the yield surface is undefined in both
86 of the models. Thus, the $\mu(I)$ model cannot be applied to granular materials in the quasi-
87 static regime.

88 This paper aims to develop a framework of constitutive modeling to unify the consti-
89 tutive theories for the solid-like and fluid-like behaviors of a granular-fluid mixture. A
90 simple shearing model is developed based on the framework by employing the Bagnold-
91 type relations for the dense flow regimes and the elastoplastic theory, a Mohr-Coulomb-
92 type relation, for the quasi-static regime. The applicability of the Mohr-Coulomb-type
93 relation to describe the solid-like behaviors is discussed. Based on the effort devoted to
94 examine Bagnold's pioneer work [9, 10, 11, 12], the constitutive relations for the macro-
95 viscous and grain-inertia regimes are modified and unified in the new model to consider
96 the dynamic behaviors. It was demonstrated that this framework provides a complete
97 description for granular-fluid materials under slow plastic deforming and fast collisional
98 shearing. In this work, dry granular flows in simple configurations are studied to get an-
99 alytical solutions based on the presented unified model. The results are compared with
100 the analytical solutions obtained using the $\mu(I)$ model. In addition, the new model is
101 employed to predict the stress-strain relations of two annular shear tests, the numerical
102 and experimental results are compared. The applicability and advantages of the unified
103 model are discussed.

104 2. Framework of the constitutive model for granular-fluid flows

105 As pointed out above, the constitutive relations (1) and (2) were developed for two
106 distinct regimes, respectively. The constitutive relation for the transition region is absence
107 so that the continuous description of the flow regimes is impossible. In granular-fluid
108 flows, the intergranular friction, collisions and the fluid viscous force are believed to
109 coexist and transfer momentum simultaneously [13]. Thus, an additive form combining
110 (1) and (2), which reflect the viscous fluid flow and the particle collisions respectively, is

111 employed for the shear stress of a dense granular-fluid flow. The total rheological shear
 112 stress T_r is the sum of T_v and T_i , i.e.

$$T_r = T_v + T_i. \quad (7)$$

113 Figure 2 shows the comparison between experimental data and numerical predictions us-
 114 ing Eq. (7). It is found that the direct additive form can correctly capture the overall
 115 dynamic behavior and provide an easy yet seamless transition. The material parame-
 116 ters introduced in Bagnold's experiments are used in the stress prediction by combining
 117 equations (1) and (2) into (7).

Figure 2: Comparison between the shear stress predicted by (7) and experimental data of $\lambda = 11$ in [5].

118 The constitutive relation for the transition regime is therefore determined. As the
 119 shear rate increases, the domination of the mechanical behaviors changes from the fluid
 120 viscosity to the particle collisions spontaneously in a dense suspension. Likewise, the
 121 total rheological normal stress P_r can be described by

$$P_r = P_v + P_i. \quad (8)$$

122 Ness & Sun [14] proposed a similar constitutive equation based on the additive form
 123 combining viscous effects with dry granular rheology. In their equation, the prolonged
 124 frictional contact and the particle collisions are not distinguished. The former is believed
 125 to be rate-independent and cannot be sufficiently described by rate-dependent rheological

models. As mentioned before, the yield stress, derived from the prolonged frictional contact, was not accounted for in the Bagnold's model since the effect of the solid particles' weight was eliminated in the experiments. For general cases of granular-fluid mixture, the contact friction in the quasi-static regime and residual stresses after failure are essential parts of a complete model. The constitutive equations for granular flows should satisfy a generalized Mohr-Coulomb type yield criterion as $dU/dy \rightarrow 0$ [15, 16]. Shibata & Mei [11] assumed the following relation for the quasi-static regime

$$T_0 = -fP_0 \operatorname{sgn}\left(\frac{dU}{dy}\right), \quad (9)$$

where T_0 and P_0 are the shear and normal stresses in the quasi-static state; f is an empirical coefficient of dynamic friction. The 'sgn' function is applied to return the sign of the shear strain rate.

The particle weight induced stresses are combined with the rheological stresses by following the additive form to yield a constitutive framework as

$$P = P_0 + P_r = P_0 + P_v + P_i, \quad (10a)$$

$$T = T_0 + T_r = T_0 + T_v + T_i. \quad (10b)$$

where P_0 and T_0 are regarded as the static portion of the framework. T_r and P_r are the dynamic portion. The framework is akin to the assumption of constitutive modeling for granular materials in [17], in which the stress tensor can be decomposed into a static (rate-independent) part and a dynamical (rate-dependent) part from the perspective of statics. The framework based on the assumption was preliminarily validated in cases of dry granular flow where the viscous terms P_v and T_v are negligible [18, 19]. The constitutive model based on this framework is capable to describe the stress state throughout the shearing process from quasi-static to high-speed shearing stage.

The framework can predict steady uniform flows over a range of bed slopes rather than only for one critical slope for dry granular flows on an inclined plane, which is consistent with the experimental observations [16, 20].

3. Constitutive model for dense granular-fluid flows

In this section, a concrete simple-shearing model for granular-fluid flow is developed based on the framework of (10). A conventional approach is employed to determine the static stresses P_0 and T_0 . The specific expression for the dynamic portion is determined by modifying the Bagnold's models. Both of the static and dynamic portions are formulated for the solid phase and therefore regarded as effective stress defined in soil mechanics. It is clear that the stresses determined by (1) and (2) will vanish when the solid volume fraction is equal to zero.

3.1. Constitutive relation for quasi-static state

As indicated by equation (9), the yield stress T_0 is proportional to the normal stress P_0 with a constant friction coefficient. The empirical friction coefficient, f , is determined as the tangent of the residual friction angle ϕ since the yield stress is assumed equal to the residual stress in the Mohr-Coulomb type relation. The friction angle can be obtained in simple shear tests [21], and is assumed independent of the shear rate. From (9), the shear stress in quasi-static stage is expressed as

$$T_0 = -P_0 \operatorname{sgn}\left(\frac{dU}{dy}\right) \tan \phi. \quad (11)$$

Once P_0 is determined, the shear stress T_0 will be obtained consequently. The normal stress P_0 usually stems from the gravity of the solid particles.

Figure 3: Schematic of a steady granular-fluid flow on an inclined plane.

Take the free surface granular-fluid flow shown in Figure 3 as an example, the normal

167 stress is the component of gravity perpendicular to the flow plane,

$$P_0 = (\rho_s - \rho_f)Cgh\cos\theta, \quad (12)$$

168 where ρ_f is the density of the fluid. It is worth to mention that the normal stress deter-
 169 mined by (12) is considered as the initial value of P_0 . The static stress P_0 will decrease
 170 with the increase of shear rate in the dense flow regime since more fierce particle colli-
 171 sions lead to less prolonged contact.

172 The simple relation (11) is widely employed as it is easy to be understood and im-
 173 plemented in numerical calculations. The expression (12) was proved applicable in the
 174 cases without shear softening (or liquefaction in saturated granular material) in the quasi-
 175 static state [22]. For the cases with excess pore pressure, more complicated constitutive
 176 theories are required for the quasi-static regime. It is stated that granular materials show
 177 rate-independent hypoplastic behaviours under monotonous deformations [23].

178 3.2. Constitutive relations for dense flow regime

179 From (1) and (2), together with (4), two dimensionless quantities are obtained as

$$\frac{T_v\rho_sd^2}{\lambda\mu^2} = 2.25B \quad (13)$$

180 and

$$\frac{T_i\rho_sd^2}{\lambda\mu^2} = (0.042 \sin \alpha_i)B^2, \quad (14)$$

181 which depend only on the Bagnold number B . These relationships cannot describe the
 182 experimental observations when the linear concentration, λ , is greater than 12 [5, 12]. It
 183 implies that the dimensionless quantities are also dependent on the linear concentration.
 184 Thus, the dimensionless quantities are extended to the following general expressions as

$$\frac{T_v\rho_sd^2}{\lambda\mu^2} = f_1(\lambda)B \quad (15)$$

185 and

$$\frac{T_i\rho_sd^2}{\lambda\mu^2} = f_2(\lambda)B^2, \quad (16)$$

186 where $f_1(\lambda)$ and $f_2(\lambda)$ are functions of λ to be specified.

187 (a) *Shear stress in the macro-viscous regime*

188 The shear stress in the macro-viscous regime is first investigated with the goal to
 189 find a constitutive model applicable in the whole spectrum of λ studied in Bagnold's
 190 experiments. For the viscous regime, Bagnold derived the expression of total shear stress
 191 as

$$\bar{T}_v = (1 + \lambda) \left[1 + \frac{1}{2} f(\lambda) \right] \mu \frac{dU}{dy}, \quad (17)$$

192 in which $\bar{T}_v$ is the total shear stress consisting of the contributions of grain and fluid,
 193 T_v and τ_v ; $f(\lambda)$ is a function of the linear concentration and reflects the amplitude of the
 194 shear velocity fluctuation, and $f(0) = 0$. In order to determine the shear stress of the solid
 195 phase, the total shear stress needs to be divided into T_v and τ_v . Bagnold assumed a simple
 196 relation for the fluid contribution in the total shear stress in the grain-inertia regime as
 197 [12, 24]

$$\tau_i = \frac{\tau_0}{(1 + \lambda)}, \quad (18)$$

198 where τ_0 is the shear stress in pure fluid and formulated as $\mu dU/dy$. The fluid contribu-
 199 tion decreases as the linear concentration increases. This relation is assumed to hold in
 200 the macro-viscous regime as well. Thus,

$$\tau_v = \frac{\mu}{(1 + \lambda)} \frac{dU}{dy}. \quad (19)$$

201 Based on (17) and (19), the contribution of grain is derived as

$$\begin{aligned} T_v &= \bar{T}_v - \tau_v \\ &= \left\{ (1 + \lambda) \left[1 + \frac{1}{2} f(\lambda) \right] - \frac{1}{1 + \lambda} \right\} \mu \frac{dU}{dy}. \end{aligned} \quad (20)$$

202 Bagnold employed $f(\lambda) = \lambda$ in (17). Thus, the expression of T_v is preliminarily deter-
 203 mined as

$$T_v = \left[(1 + \lambda) \left(1 + \frac{1}{2} \lambda \right) - \frac{1}{1 + \lambda} \right] \mu \frac{dU}{dy}. \quad (21)$$

204 The dimensionless quantity derived from (21) is

205

$$\frac{T_v \rho_s d^2}{\lambda \mu^2} = \left(\lambda^{-\frac{3}{2}} + \frac{3}{2} \lambda^{-\frac{1}{2}} + \frac{1}{2} \lambda^{\frac{1}{2}} + \frac{\lambda^{-\frac{3}{2}}}{1 + \lambda} \right) B, \quad (22)$$

206 which demonstrates a concrete formula of the proposition of (15). The model (21) is
 207 capable to predict the experimental results for granular-fluid mixture with high concen-
 208 tration to some extent. For exact prediction, a further modification is needed.

Figure 4: Schematic of a simple-shearing granular-fluid flow with a stagnant zone.

209 A well-known phenomenon in granular-fluid flows is that the shear stress is relatively
 210 insensitive to the solid volume fraction C when the value of C is below approximately 0.5,
 211 but increases rapidly when the solid volume fraction exceeds this critical value [6]. Some
 212 researchers [25, 26] used a power series of the volume fraction (or the linear concentra-
 213 tion) combined with an exponential term to describe the dynamic viscosity of granular-
 214 fluid mixture. These expressions were determined by fitting shear stress versus shear
 215 strain rate curves. The mechanism of the phenomenon needs further clarification. As
 216 pointed out by Bagnold [5] and Hanes & Inman [6], the solid volume fraction must be
 217 less than a critical value C_c to assure a full shearing to occur. The critical value was found
 218 to depend on the packing pattern and lay between 0.53 and 0.65 [11, 24]. For the general
 219 case of a gravity flow shown in Figure 4, a stagnant zone with thickness of $H - h$ will
 220 arise at the bottom of the specimen when the mean solid volume fraction C is greater than
 221 C_c . If the total thickness H rather than that of the flowing zone h is used in the calcula-
 222 tion of the shear strain rate, an underestimated result will be obtained. In a steady flow

with $C > C_c$, the exchange of particles between the flowing and the stagnant zone reaches a balance. The mean solid volume fraction in the upper layer, C_f , is deduced to be unchanged as the critical value C_c . The mean value of the stagnant zone C_s should be greater than C_c to keep static. Otherwise, solid particles will move from the stagnant zone to the flowing zone till C_f reaches the value of C_c . Thus, the experimental observation that the shear stress increases dramatically when the solid volume fraction exceeds the critical value C_c is attributed to both the increase of the dynamic viscosity and the decrease of the thickness of the flowing zone. Therefore, the critical value of solid volume fraction should be taken into account in the simple-shearing model for dense granular-fluid flow. Inspired by the way to take the critical value into account in [11], the following model is proposed for the macro-viscous regime.

$$T_v = K_1 \frac{dU}{dy}, \quad (23)$$

where

$$K_1 = \left[(1 + \lambda) \left(1 + \frac{1}{2} \lambda \right) - \frac{1}{1 + \lambda} \right] \mu \left(1 - \frac{C}{C_c} \right)^{-n} \quad (24)$$

is called effective viscosity; n is a fitting parameter. In Shibata & Mei's work [11], it was chosen $n = 1$.

(b) Shear stress in the grain-inertia regime

The constitutive equation for the grain-inertia regime is slightly modified based on the Equation (16). The experimental results in [5] show that shear stresses in different regimes deviate as a whole with the change of the linear concentration in the logarithm coordinates of $\rho_s d^2 (dU/dy)^2$ versus grain shear stress. It is assumed that the shear stress T_i changes in the same rate with T_v when the value of λ varies. Based on this assumption, the original equation for the 'grain-inertia' regime, (2), is modified to be

$$T_i = K_2 \left(\frac{dU}{dy} \right)^2, \quad (25)$$

where

$$K_2 = 0.042 R_v \rho_s (\lambda d)^2 \sin \alpha_i \quad (26)$$

245 and

$$R_v = \frac{K_1}{k_1} = \frac{\left[(1 + \lambda) \left(1 + \frac{1}{2} \lambda \right) - \frac{1}{1 + \lambda} \right] \left(1 - \frac{c}{c_c} \right)^{-n}}{2.25 \lambda^{\frac{3}{2}}} \quad (27)$$

246 is termed as correction factor.

247 3.3. A simple-shearing model for dense granular-fluid mixture

248 Substituting (23) and (25) into (7) yields the expression of shear stress in the dense
249 flow regime

$$T_r = K_1 \frac{dU}{dy} + K_2 \left(\frac{dU}{dy} \right)^2. \quad (28)$$

250 Based on (5), (6) and (8), the normal stress in the flowing state is expressed as

$$P_r = \frac{K_1}{\tan \alpha_v} \frac{dU}{dy} + \frac{K_2}{\tan \alpha_i} \left(\frac{dU}{dy} \right)^2. \quad (29)$$

251 The modified models are capable of describing the mechanical behaviors of a dense
252 granular-fluid mixture from the 'macro-viscous' regime to the 'grain-inertia' regime. As
253 shown in Figure 5, by choosing $n = 0.2$ and $C_c = 0.65$ [6], (28) and (29) can predict
254 Bagnold's experimental results with satisfactory agreement.

255 Furthermore, based on the framework (10), the dynamic stresses (28) and (29) are
256 combined with the static stresses T_0 and P_0 , respectively, to obtain a simple-shearing
257 model as

$$P = P_0 + \frac{K_1}{\tan \alpha_v} \frac{dU}{dy} + \frac{K_2}{\tan \alpha_i} \left(\frac{dU}{dy} \right)^2, \quad (30a)$$

$$T = -P_0 \operatorname{sgn} \left(\frac{dU}{dy} \right) \tan \phi + K_1 \frac{dU}{dy} + K_2 \left(\frac{dU}{dy} \right)^2. \quad (30b)$$

258 This is a simple example of the unified model for granular-fluid mixture in the quasi-static
259 and dense flow regimes. The rate-independent constitutive component for the unified
260 model can be chosen according to the requirement in comprehensively modeling the
261 behaviors inside the yield surface.

(a)

(b)

Figure 5: Comparison between the stresses predicted by (28) and (29) with $n = 0.2$ and $C_c = 0.65$ and the data from (a) the figure 3 and (b) the figure 4 in [5]. The experimental data are indicated by various symbols. The dashed lines (upper panel) denote the shear stresses while the solid lines (lower panel) are the normal stresses.

4. Analytical solutions for steady granular flows

Three dry granular flows under simple configurations are studied. Analytical solutions from the simple-shearing model are compared to the solutions from the $\mu(I)$ model.

4.1. Plane shear flow

Consider shearing of a granular material made of particles with diameter d and density ρ_s , as shown in Figure 1. The confining pressure P is imposed on the top plate. The granular material is sheared at a prescribed rate $\dot{\gamma} = U/h$, where U is the velocity of the top plate and h is the depth of the granular body. Gravity is not considered. To maintain a steady plane shear, the shear force on the top plate depends on the imposed confining pressure and shear rate.

In the $\mu(I)$ model, the inertial number can be calculated through

$$I = \frac{d\dot{\gamma}}{\sqrt{P/\rho_s}}. \quad (31)$$

Consequently, we can obtain the shear stress T by [7]

$$T = \mu(I)P, \text{ with } \mu(I) = \mu_1 + \frac{\mu_2 - \mu_1}{I_0/I + 1}, \quad (32)$$

where μ_1 , μ_2 and I_0 are three parameters of the $\mu(I)$ model.

With the presented unified model, considering the steady shearing of dry granular materials where the viscous terms are negligible, we have the following two expressions

$$T = \sigma_{yy}^f \sin \phi + K_2 \dot{\gamma}^2, \quad (33)$$

and

$$P = \sigma_{yy}^f + \frac{K_2}{\tan \alpha_i} \dot{\gamma}^2. \quad (34)$$

The frictional shear stress is computed as $\sigma_{yy}^f \sin \phi$, instead of $\sigma_{yy}^f \tan \phi$, because simulations of plane shear flows indicate that the difference between the vertical and the horizontal normal stress is very small, i.e., $\sigma_{xx}^f \approx \sigma_{zz}^f$ [28, 29]. The frictional shear stress

281 is then equal to $\sigma_{yy}^f \sin \phi$. Based on Eqs. (33) and (34), the total shear force is obtained as

$$T = P \sin \phi + K_2 \dot{\gamma}^2 \left(1 - \frac{\sin \phi}{\tan \alpha_i}\right). \quad (35)$$

282 Comparing Eqs. (32) and (35), it can be observed that the shear stresses obtained by
 283 using the $\mu(I)$ model and the unified model have a similar structure. Both results consist
 284 of two parts, one part is constant with given normal stress P , and the other one depends on
 285 the shear rate. In the dense flow regime, the shear stress obtained using the $\mu(I)$ model
 286 ranges from $\mu_1 P$ to $\mu_2 P$. On the other hand, in the dense flow regime, the dispersive
 287 pressure $P_i = K_2 \dot{\gamma}^2 / \tan \alpha_i$ is from 0 to P ; therefore, the range of shear stress obtained
 288 using the unified model is from $P \sin \phi$ to $P \tan \alpha_i$. It is observed that the constants $\sin \phi$
 289 and $\tan \alpha_i$ in the unified model are equivalent to the constants μ_1 and μ_2 in the $\mu(I)$
 290 model.

291 Both of the models enable precise classifications of the three flow regimes of dry
 292 granular materials: quasi-static, dense flow and gaseous. Small values of $\dot{\gamma}$ ($\dot{\gamma} \rightarrow 0$)
 293 correspond to the quasi-static regime in the sense that deformation is very slow. In the
 294 $\mu(I)$ model, the threshold of I corresponds to the rapid and dilute flow regime is $I \approx 1$,
 295 which is obtained from experiments [29]. Contrarily, in the unified model, the gaseous
 296 regime can be theoretically determined: it corresponds to the state when the network
 297 of frictional contacts disappears, that is, when $\sigma_{yy}^f = 0$. Based on the aforementioned
 298 analysis, the shear rate corresponds to the dense flow regime in the plane shear is

$$\begin{aligned} \text{for the } \mu(I) \text{ model : } 0 < \dot{\gamma} &\lesssim \sqrt{P} / \sqrt{\rho_s d^2}, \\ \text{for the unified model : } 0 < \dot{\gamma} &< \sqrt{P} / \sqrt{K_2}. \end{aligned} \quad (36)$$

299 Again, the ranges of shear rate corresponding to the dense flow regime obtained using
 300 the $\mu(I)$ model and the unified model have similar form. Note that the constant K_2 is
 301 related to particle diameter, density and solid volume fraction. It can be observed that in
 302 both of the models, the upper limits of the shear rate depend on the confining pressure P
 303 and physical properties of the granular material.

304 Although these two models bear some similarities, there are fundamental differences.
 305 The $\mu(I)$ model employs an inertial-number-dependent phenomenological frictional co-

efficient, which changes with shear rate and confining pressure. However, the model does not give any clue why the phenomenological frictional coefficient $\mu(I)$ changes with different shear rate and confining pressure. On the other hand, the unified model explicitly considers the origin of different stress components. In the unified model, the change of phenomenological frictional coefficient can find its explanation as follows. The ratio between shear stress and normal stress in the network of frictional contacts is related to the internal friction angle ϕ of the material, whereas the ratio of the collision-induced shear/normal stresses is related to another angle α_i . Experiments show that α_i is generally larger than ϕ . Therefore, when the flow state moves from the quasi-static regime to the gaseous regime, the collision-induced stresses becomes more and more significant. In this process, the phenomenological frictional coefficient increases from $\sin \phi$ to $\tan \alpha_i$. The evolution of the phenomenological frictional coefficient in the two models is written, respectively, as

$$\begin{aligned} \text{in the } \mu(I) \text{ model : } \mu &= \mu_1 + \frac{\dot{\gamma}d(\mu_1 - \mu_2)}{I_0\sqrt{P/\rho_s} + \dot{\gamma}d}, \\ \text{in the unified model : } \mu &= \sin \phi + \frac{\dot{\gamma}^2 K_2 (\tan \alpha_i - \sin \phi)}{P \tan \alpha_i}. \end{aligned} \quad (37)$$

Comparing Eq. (37) with Eq. (32), the evolutions of the phenomenological frictional coefficient in the two models have a similar structure, but different dependences on shear rate and confining pressure.

4.2. Vertical chute flow

Consider a granular material flowing between two vertical plates with a distance of $2W$, as shown in Figure 6. The confining pressure on the two vertical plates is P , which implies that $\sigma_{xx} = P$ within the flow in the steady state.

According to the unified model, the possible range of shear stress τ_{xy} in the chute flow is from $P \sin \phi$ to $P \tan \alpha$. Because of symmetry, the shear stress at the center of the flow is zero. Based on the force balance along the x axis, the shear stress can be written as

$$\tau_{xy} = \rho g x, \quad (38)$$

Figure 6: Schematic of vertical chute flow.

where ρ is the bulk density of the granular material. The steady flow condition requires that the shear stress increases linearly from the flow center to the vertical plates. Consequently, there exists an unsheared zone in which $\tau_{xy} < P \sin \phi$. Namely, when $x < x_p$ ($x_p = P \sin \phi / \rho g$), the granular material is unyielded and moves as a plug layer. If $x_p > W$, the whole granular body is unyielded and no granular flow is possible. Furthermore, the maximum shear stress required for the force balance does not exceed the maximum shear stress that can be provided, i.e. $\tau_{xy} < P \tan \alpha_i$. Therefore, according to the unified model, a steady granular flow is possible in the vertical chute only if

$$\rho g W / \tan \alpha_i < P < \rho g W / \sin \phi. \quad (39)$$

Now we proceed to derive the velocity profile of the steady flow. The stress components for the present vertical chute flow, as specified in (33) and (34) for the plane shear flow, take the forms

$$\begin{aligned} P &= \sigma_{xx}^f + \frac{K_2}{\tan \alpha_i} \left(\frac{dU_y}{dx} \right)^2, \\ \tau_{xy} &= \sigma_{xx}^f \sin \phi + K_2 \left(\frac{dU_y}{dx} \right)^2. \end{aligned} \quad (40)$$

Substituting Eq. (40) into Eq. (38), we have

$$\left(\frac{dU_y}{dx} \right)^2 = \frac{(\rho g x - P \sin \phi) \tan \alpha_i}{K_2 (\tan \alpha_i - \sin \phi)}. \quad (41)$$

Solving the above equation using the boundary condition $U_y = 0$ at $x = W$, we can obtain

the velocity profile

$$U_y(x) = U_y^p + \frac{2\sqrt{\tan \alpha_i}(\rho g x - P \sin \phi)^{3/2}}{3\sqrt{K_2}(\tan \alpha_i - \sin \phi)\rho g} \quad \text{if } x_p \leq x \leq W, \quad (42)$$

where U_y^p is the velocity of the unsheared plug layer

$$U_y^p = -\frac{2\sqrt{\tan \alpha_i}(\rho g W - P \sin \phi)^{3/2}}{3\sqrt{K_2}(\tan \alpha_i - \sin \phi)\rho g} \quad \text{if } x < x_p. \quad (43)$$

Analytical solutions can also be obtained using the $\mu(I)$ model [30]. Similarly, an unsheared plug layer exists, and there is a confining pressure range, only with confining pressure in this range a steady granular flow is possible. If the parameters in the $\mu(I)$ model are taken as $\mu_1 = \sin \phi$ and $\mu_2 = \tan \alpha_i$, the width of the plug layer and the range of the confining pressure are identical to those obtained from the unified model. However, the velocity profiles obtained using these two models are not identical.

To quantitatively compare the solutions obtained using these two models, the velocity profiles are calculated. The following material properties are used: $\rho = 1470 \text{ kg/m}^3$, $\rho_s = 2450 \text{ kg/m}^3$ and $d = 0.002 \text{ m}$. The parameters for the $\mu(I)$ model are chosen as $\mu_1 = 0.38$, $\mu_2 = 0.64$ and $I_0 = 0.279$. For the unified model, we take $\sin \phi = \mu_1$, $\tan \alpha = \mu_2$ and $K_2 = 0.2$. The width of the chute is 0.2 m , the confining pressure P is 3000 Pa . Owing to the symmetric geometry, only the right half of the granular material is considered. The calculated results are shown in Figure 7. Using the given parameters, the two models predict identical unsheared velocity. However, the velocity profiles in the shear zone are somewhat different.

4.3. Flow on an inclined plane

The problem of a granular mass on an incline is considered. As shown in Figure 3, the granular mass has a free surface and is subjected to gravity. The inclination angle is θ . The height of the granular layer is h .

For this steady granular flow, the stress distribution should be hydrostatic

$$\sigma_{yy} = \rho g(h - y) \cos \theta, \quad \sigma_{xy} = \rho g(h - y) \sin \theta. \quad (44)$$

Figure 7: Velocity profiles obtained using the unified model and the $\mu(I)$ model in the vertical chute flow.

364 For an infinite inclined plane, we assume that the frictional stresses $\sigma_{yy}^f = \sigma_{xx}^f$ in the
 365 flowing state; thus, the shear/normal stress ratio of the frictional contacts is $\tau_{xy}^f / \sigma_{yy}^f =$
 366 $\sin \phi$.

367 The following force balance must be satisfied in the steady state

$$\begin{aligned}\sigma_{yy} &= \rho g(h-y) \cos \theta = \sigma_{yy}^f + \frac{K_2}{\tan \alpha_i} \left(\frac{dU}{dy} \right)^2, \\ \tau_{xy} &= \rho g(h-y) \sin \theta = \sigma_{yy}^f \sin \phi + K_2 \left(\frac{dU}{dy} \right)^2.\end{aligned}\tag{45}$$

368 Here, once again, the stress consists of the contributions from frictional contacts and
 369 collisions, described by the Mohr-Coulomb model and the Bagnold-type rheology, re-
 370 spectively. Based on the force balance equations, the following differential equation is
 371 derived

$$(1 - \sin \phi / \tan \alpha_i) K_2 \left(\frac{dU}{dy} \right)^2 - \rho g(\sin \theta - \cos \theta \sin \phi)(h-y) = 0.\tag{46}$$

372 Solving the above equation, the velocity profile is obtained as

$$U(y) = \frac{2}{3} \sqrt{\frac{\rho g(\sin \theta - \cos \theta \sin \phi)}{(1 - \sin \phi / \tan \alpha_i) K_2}} (h^{3/2} - (h-y)^{3/2}).\tag{47}$$

373 The velocity profile, evolving as $(h - y)^{3/2}$, corresponds to the Bagnold profile. Once the
 374 velocity is obtained, the stress components from frictional contacts and collisions can be
 375 determined. From the velocity profile it is noted that velocity and shear rate increase with
 376 the inclination θ . With increasing θ , the normal and shear stress induced by collisions
 377 become more significant. This increase in the dispersive normal stress results in a trend
 378 of dilation, tending to reduce the stress components caused by frictional contacts.

379 If the granular material is modeled using the $\mu(I)$ model, dense granular flow can only
 380 happen if the inclination θ is between $\tan^{-1} \mu_1$ and $\tan^{-1} \mu_2$. With the unified model, a
 381 similar inclination range can be derived as follows

$$\tan \theta = \frac{\tau_{xy}}{\sigma_{yy}} = \sin \phi + \frac{\sigma_{zz}^c}{\sigma_{zz}} (\tan \alpha_i - \sin \phi), \quad (48)$$

382 where σ_{zz}^c is the dispersive normal stress. The steady dense flow condition requires
 383 $0 < \sigma_{zz}^c < \sigma_{zz}$, because if $\sigma_{zz}^c > \sigma_{zz}$ the network of frictional contacts disappears com-
 384 pletely, which means that the granular material enters the gaseous regime. Consequently,
 385 according to the unified model, the inclination range for dense granular flow is

$$\tan^{-1}(\sin \phi) < \theta < \alpha_i, \quad (49)$$

386 which is exactly the inclination range derived from the $\mu(I)$ model. It is easily seen that
 387 the obtained velocity profile is valid only under the condition (49).

388 The velocity profiles of the granular flow with two different inclinations are cal-
 389 culated. The material parameters used in the calculation are the same as those used
 390 in the former vertical chute flow. For the unified model, the parameters are taken as
 391 $\sin \phi = \mu_1 = 0.38$ and $\tan \alpha_i = \mu_2 = 0.64$. Figure 8 shows the results obtained using
 392 $K_2 = 0.3$ for $\theta = 23^\circ$, and $K_2 = 0.1$ for $\theta = 25^\circ$. Using the given parameters, the two
 393 models provide similar predictions.

394 5. Performance of the proposed model

395 In this section, the performance of the unified simple shear model is demonstrated
 396 by modeling two tests, respectively, for a dry granular flow and a granular-fluid mixtures
 397 flow.

Figure 8: Velocity profiles obtained using the unified model and the $\mu(I)$ model in the flow on inclined plate.

5.1. Case 1: Dry granular materials

The experimental results of dry granular materials sheared in an annular shear cell were reported by Savage & Sayed [21]. In the experiments, the shear velocity was adjusted to keep the height of the granular mass constant and thus keep the volume unchanged. This steady state is equivalent to an undrained simple shear of saturated granular materials. The experimental data for 1.0 mm spherical polystyrene beads are predicted by the new model. The shear stresses were measured on the top surface of the sample. As stated in [21], the loads applied by the upper disk range from 100 to 1500 N/m². However, the specific load for each single sample was not reported. By checking the measured normal stress for 1.0 mm beads, we assume that the normal stress in the quasi-static regime P_0 has a value around 100 N/m² which is also regarded as the residual normal stress after yielding. As mentioned before, the theoretical maximum value of solid volume fraction, C_0 , will be replaced by the asymptotic limit of the maximum measured solid volume fraction, C_∞ , in the calculation for a specific experiment. Since the exact value of C_∞ was not reported in Savage & Sayed's work, we use 0.65 which is a typical value for monosized spheres [6, 24]. The critical volume fraction C_c is approximately 0.62 [11]. All the parameters for the prediction are listed in Table 1 and Table 2.

As shown in Figure 9, the predicted curves can fit the experimental data at high

Table 1: Parameters for the shear tests of 1.0 mm beads in [21]

d	C_∞	C_c	ρ_s	ρ_f	μ	ϕ	θ
[mm]	[-]	[-]	[kg/m ³]	[kg/m ³]	[Pa · s]	[°]	[°]
1.0	0.65	0.62	1095	1.29	1.83×10^{-5}	23	0

Table 2: Stress ratios measured in the shear tests of 1.0 mm beads in [21]

C	$\tan \alpha_v$	$\tan \alpha_i$
[-]	[-]	[-]
0.461	0.50	0.51
0.483	0.40	0.51
0.504	0.30	0.51
0.524	0.30	0.51

417 shear strain rate very well. For the dense specimen, the non-quadratic dependence of
 418 the stresses on the shear rate in the slow shear stage is also captured by the new model.
 419 However, the predicted results for the specimens with $C < 0.524$ show a slight over-
 420 estimation, especially in the slow shear stage. The assumed value of P_0 , 100 N/m²,
 421 is believed to be greater than the real value of the tests with $C < 0.524$. However, as
 422 mentioned before, $P_0 = 100$ N/m² is the minimum value which can be imposed on the
 423 specimens by the upper disk. A plausible explanation is that shear softening occurs in the
 424 relatively loose specimens under undrained condition. In this case, the normal stress P_0
 425 which corresponds to the effective stress in soil mechanics would decrease to a residual
 426 value to eliminate the tendency of volume compression. A looser specimen will present
 427 lower residual strength. The Mohr-Coulomb type relations (11) and (12), used as the
 428 static portion of (30), cannot capture the decrease of P_0 in the quasi-static stage. How-
 429 ever, the dynamic portion is validated in the describing of the stress-strain rate relations
 430 for dry granular flows with different solid volume fraction.

(a)

(b)

Figure 9: Elementary modeling results for dry granular flow with different grain linear concentration: (a) normal stress and (b) shear stress. The experimental data are indicated by various symbols. The dashed lines (upper panel) denote the normal stresses while the solid lines (lower panel) are the shear stresses, predicted by the postulated model

5.2. Case 2: Granular-water mixture

Another elementary modeling by the unified simple-shearing model is based on the laboratory tests from Hanes & Inman [6] with spherical particles sheared in water. The data for particles with diameter of 1.85 mm are selected since they are claimed to be of good quality. The maximum measured volume fraction for 1.85 mm particles was reported to be 0.55 [6]. The asymptotic limit C_∞ is presumed to be approximately 0.61. The critical volume fraction is assumed to be 0.52 as a partially shearing with $C = 0.53$ was reported. The load from the upper disk, P_0 , is about 200 N/m². The angle α_v is equal to the dynamic angle of repose, 28°. All the parameters are listed in Table 3 and Table 4.

Table 3: Parameters for the shear tests of 1.85 mm beads in [6]

d	C_∞	C_c	ρ_s	ρ_f	μ	ϕ	θ
[mm]	[-]	[-]	[kg/m ³]	[kg/m ³]	[Pa · s]	[°]	[°]
1.85	0.61	0.52	2780	1000	1.0×10^{-3}	0.59	0

Table 4: Stress ratios measured in the shear tests of 1.85 mm beads in [6]

C	$\tan \alpha_v$	$\tan \alpha_i$
[-]	[-]	[-]
0.49	0.53	0.59
0.51	0.53	0.59

The predicted results are shown in Figure 10. The predicted curves of $C = 0.51$ show a good agreement with the experimental data. The stresses of the specimen with $C = 0.49$ are slightly overestimated. Similar to the case 1, the overestimation of P_0 and T_0 may be responsible for this discrepancy. Nevertheless, the dynamic portion of the presented model is capable of describing the stress versus shear rate relation in the dense flow regime for a granular-water mixture.

(a)

(b)

Figure 10: Elementary modeling results for granular-water flow with different solid volume fraction: (a) normal stress and (b) shear stress. The experimental data are indicated by various symbols. The solid lines denote the normal stresses in the upper panel and the shear stresses in the lower panel, predicted by the postulated model.

6. Conclusions

A framework for the constitutive modeling of granular-fluid mixture is developed by combining a rate-independent static part with a rate-dependent rheological part in an additive form. In this framework, the effect of the prolonged contact, the viscosity of the interstitial fluid and the particle collisions are considered explicitly. The Mohr-Coulomb-type relation for the quasi-static regime and the Bagnold-type rheological model for the dense flow regime are unified in the framework to obtain a simple-shearing model which can describe the mechanical behaviors throughout the shear process from yielding to high-speed shearing. In the modified Bagnold-type model, the conversion between the so-called macro-viscous and grain-inertia regimes can be captured continuously. The critical solid volume fraction to assure the occurrence of a full shearing is taken into account. The existence of the stagnant zone is identified as the main reason for the dramatic increase of the dynamic viscosity as the solid volume fraction exceeds the critical value.

Analytical solutions for dry granular flows in three configurations, i.e., plane shear, vertical chute flow and flow on inclined plate, are derived based on the presented model. The solutions are compared with those obtained using the $\mu(I)$ model. The following observations can be made. (1) Both models show that in order to switch from the quasi-static to the gaseous regime, one can either increase the shear rate or decrease the pressure. (2) The overall phenomenological frictional coefficient is dependent on flow kinematics, material properties and boundary conditions. In both models there are lower and upper limits for this phenomenological frictional coefficient. The $\mu(I)$ model shows that the friction angle increases as the granular material approaches the gaseous regime, but does not give a physical background. The presented unified model shows that the increase in the phenomenological frictional coefficient is because of particle collisions.

The developed model is used to predict the stress-strain rate relations of two granular-fluid flows. The predicted results for specimens with different solid volume fraction show a good agreement with the experimental data in the high shear rate stage. However, when the static (or residual) normal stress in the beginning of the flowing is determined as the component of gravity or the external load on the solid phase, the total stresses in the low shear rate stage is overestimated by the new model for the relatively loose specimens. A possible explanation is that shear softening occurs in the relatively loose specimens in

478 the quasi-static regime and the Mohr-Coulomb model cannot capture this behavior.

479 Nevertheless, the unified model has some favourable distinct features. First, the quasi-
480 static solid-like behaviors of granular materials are fully defined in the rate-independent
481 part of the model. The modeling of the quasi-static regime, such as critical state, plas-
482 tic flow and nonlinear elasticity, can be further improved by changing the static part in
483 the unified model to more sophisticated models. Thus, the model is quite flexible for a
484 modification. Second, granular materials in the quasi-static and dense flow regime can be
485 described using the model uniformly, which simplifies numerical implementation. Third,
486 the model reveals that in the dense flow regime, especially when granular materials are
487 quite close to the gaseous regime, particle collisions contribute to a significant part of the
488 stress.

489 **Acknowledgements**

490 The authors wish to thank the financial support from the National Natural Science
491 Foundation of China (grant number 51809230 and 51709230), the European Commis-
492 sion 7th Framework Programme project MUMOLADE (289911), and the H2020 Marie
493 Skłodowska-Curie Actions RISE 2017 HERCULES (778360) and FRAMED (734485).

494 **Conflict of interest:**

495 The authors declare that they have no conflict of interest.

496 **References**

- 497 [1] Fang, C. and Wu, W.: On the weak turbulent motions of an isothermal dry granular
498 dense flow with incompressible grains: part I. Equilibrium turbulent closure models.
499 *Acta Geotechnica*. 9, 725-737 (2014)
- 500 [2] Fang, C. and Wu, W.: On the weak turbulent motions of an isothermal dry gran-
501 ular dense flow with incompressible grains: part II. Complete closure models and
502 numerical simulations. *Acta Geotechnica*. 9, 739-752 (2014)
- 503 [3] Nedderman, R. M.: Statics and kinematics of granular materials. Cambridge Uni-
504 versity Press, (1992)

- 505 [4] Calvetti, F. and Prisco, C. D. and Redaelli, I. and Sganzerla, A. and Vairaktaris, E.:
506 Mechanical interpretation of dry granular masses impacting on rigid obstacles. *Acta*
507 *Geotechnica*. 14:1289-1305 (2019)
- 508 [5] Bagnold, R. A.: Experiments on a gravity-free dispersion of large solid spheres in
509 a Newtonian fluid under shear. *Proc. R. Soc. Lond. A Math. Phys. Sci.* 225, 49-63
510 (1954)
- 511 [6] Hanes, D. M. and Inman, D. L.: Observations of rapidly flowing granular-fluid
512 materials. *Journal of Fluid Mechanics*. 150, 357-380 (1985)
- 513 [7] Jop, P. and Forterre, Y. and Pouliquen, O.: A constitutive law for dense granular
514 flows. *Nature*. 441.7094, 727-730 (2006).
- 515 [8] Boyer, F. and Guazzelli, E. and Pouliquen, O.: Unifying suspension and granular
516 rheology. *Physical Review Letters*. 107, 188301 (2011)
- 517 [9] Bailard, J. A. and Inman, D. L.: A reexamination of Bagnold's granular-fluid model
518 and bed load transport equation. *J. Geophys Res.* 84, 7827-7833 (1979)
- 519 [10] Mctigue, D. F. and Savage, S. B.: Comment on A reexamination of Bagnolds
520 granular-fluid model and bed load transport equation by J. A. Bailard and D. L.
521 Inman. *J. Geophys. Res.* 86, 4311-4313 (1981)
- 522 [11] Shibata, M. and Mei, C. C.: Slow parallel flows of a water-granular mixture under
523 gravity, part I:continuum modeling. *Acta Mech.* 63, 179-193 (1986)
- 524 [12] Hunt, M. L. and Zenit, R. and Campbell, C. S. and Brennen, C. E.: Revisiting the
525 1954 suspension experiments of R. A. Bagnold. *Journal of Fluid Mechanics*. 452,
526 1-24 (2002)
- 527 [13] Iverson, R. M.: The physics of debris flows. *Reviews of Geophysics*. 35(3), 245-296
528 (1997)
- 529 [14] Ness, C. and Sun, J.: Flow regime transitions in dense non-Brownian suspensions:
530 Rheology, microstructural characterization, and constitutive modeling. *Physical Re-*
531 *view E*. 91, 012201 (2015)

- 532 [15] Cowin, S. C.: Constitutive relations that imply a generalized Mohr-Coulomb crite-
533 rion. *Acta Mech.* 20, 41-46 (1974)
- 534 [16] Savage, S. B.: Gravity flow of cohesionless granular materials in chutes and chan-
535 nels. *J. Fluid Mech.* 92, 53-96 (1979)
- 536 [17] Wu, W.: On high-order hypoplastic models for granular materials. *Journal of Engi-
537 neering Mathematics.* 56, 23-34 (2006)
- 538 [18] Guo, X. and Peng, C. and Wu, Wei and Wang, Y.: A hypoplastic constitutive model
539 for debris materials. *Acta Geotechnica.* 11, 1217-1229 (2016)
- 540 [19] Peng, C. and Guo, X. and Wu, Wei and Wang, Y.: Unified modelling of granular
541 media with Smoothed Particle Hydrodynamics. *Acta Geotechnica.* 11, 1231-1247
542 (2016)
- 543 [20] Bailard, J. A.: An experimental study of granular fluid flow. Ph.D. thesis, Univ. of
544 Calif., La Jolla. (1978)
- 545 [21] Savage, S. B. and Sayed, M.: Stresses developed by dry cohesionless granular ma-
546 terials sheared in an annular shear cell. *J. Fluid Mech.* 142, 391-430 (1984)
- 547 [22] Jop, P. and Forterre, Y. and Pouliquen, O.: Initiation of granular surface flows in a
548 narrow channel. *Phys. Fluids.* 19, 088102 (2007)
- 549 [23] Gudehus G.: Granular solid dynamics with eutaxy and hysteresis. *Acta Geotech-
550 nica.* 10, 1-15 (2019)
- 551 [24] Bagnold, R. A.: The flow of cohesionless grains in fluids. *Proc. R. Soc. Lond. A.*
552 249, 235-297 (1956)
- 553 [25] Eyring, H. and Henderson, D. and Stover, B. J. and Eyring, E. M.: *Statistical Me-
554 chanics and Dynamics.* Wiley, (1964)
- 555 [26] Thomas, D. G: Transport characteristics of suspension: VIII. A note on the viscosity
556 of Newtonian suspensions of uniform spherical particles. *J. Colloid Sci.* 20, 267-
557 277 (1965)

- 558 [27] Wang, Y. and Hutter, K.: Granular material theories revisited. In: Balmforth,
559 N. J. and Provenzale, A. (eds.) Geomorphological Fluid Mechanics. pp. 79-107.
560 Springer, (2001)
- 561 [28] da Cruz, F., Emam, S., Prochnow, M., Roux, J., & Chevoir, F.: Rheophysics of
562 dense granular material: discrete simulation of plane shear flows. *Physical Review*
563 *E.* 72(2), 021309 (2005)
- 564 [29] Andreotti, B. and Forterre, Y. and Pouliquen, O.: Granular media: between fluid
565 and solid. Cambridge University Press (2013)
- 566 [30] Chambon, G. and Bouvarel, R. and Laigle, D. and Naaim, M.: Numerical simula-
567 tions of granular free-surface flows using smoothed particle hydrodynamics. *Journal*
568 *of Non-Newtonian Fluid Mechanics.* 166(12), 698–712 (2011)